


Industrial platform scale KERN EOC





Robust and high-resolution platform scale with practical Flip/Flop display device for greatest ease of use



Weighing instead of counting!
Because the counting function is so easy to use, you can rapidly record large numbers of small parts – which saves time and money

Practical Flip/Flop display device: flexible positioning e.g. free-standing or screwed to the wall (optional). By rotating the upper housing shell you can determine the angle of the display as well as the cable outlet.
Factory Option ex works for an additional cost, delivery time + 2 working days, KERN KIB-M01, see Accessories on the right, please indicate when placing your order

Industrial platform scale KERN EOC



Features

- High mobility: thanks to rechargeable battery operation (optional), compact, lightweight construction, it is suitable for the use in several locations (laboratory, production, quality control, commissioning etc.)
- **1** Platform: weighing plate stainless steel, painted steel base, silicone-coated aluminium load cell, protection against dust and water splashes IP65. Level indicator and levelling feet for precise levelling of the scale, fitted as standard, to give the most accurate weighing result
- Weighing with tolerance range (checkweighing): a visual and audible signal helps with portioning, dispensing or grading
- Hold function: When the weighing conditions are unstable, a stable weight is calculated determining an average value
- Benchtop stand incl. wall mount for display device as standard
- Protective working cover included with delivery

- Searching and remote control of the balance using external control devices or computers with the KERN Communication Protocol (KCP). KCP is a standardised interface command structure for KERN balances and other instruments which allows you to recall and manage all relevant parameters and device functions. You can therefore simply connect KERN devices with KCP to computers, industrial control systems and other digital systems. In a large number of cases the KCP is compatible with the MT-SICS protocol.

Technical data

- Large backlit LCD display, digit height 25 mm
- Weighing plate dimensions W×D×H
 - A** 300×300×110 mm
 - B** 500×400×120 mm, see larger picture
 - C** 600×500×150 mm
 - D** 950×500×60 mm
- Dimensions of display device W×D×H 268×115×80 mm
- Permissible ambient temperature -10 °C/40 °C

Accessories

- Protective working cover, scope of delivery: 5 items, KERN EOC-A01S05
- Internal rechargeable battery pack, operating time up to 43 h without backlight, charging time approx. 3 h, KERN KFB-A01
- **2** Stand to elevate display device, height of stand approx. 330 mm, KERN EOC-A05
- **3** Mount to fasten the display device to the platform, KERN EOC-A03
- Benchtop stand incl. wall mount for display device, KERN EOC-A04
- Conversion of the display device, to move the cable outlet to the front of the display device, ideal e.g. for subsequent wall installation of the display device (standard configuration ex works: rear outlet), Factory Option, delivery time + 2 working days, KERN KIB-M01

STANDARD
























OPTION



Model	Weighing capacity [Max] kg	Readability [d] g	Smallest part weight [Normal] g/piece	Cable length approx. m	Net weight approx. kg	Weighing plate	Option	
							DAkkS	Calibr. Certificate
KERN							DAkkS	KERN
EOC 6K-3	3 6	1 2	2,5	3	6	A	963-128	
EOC 10K-3	6 12	2 5	5	3	7	A	963-128	
EOC 30K-3	15 35	5 10	10	3	6	A	963-128	
EOC 30K-3L	15 35	5 10	10	3	9	B	963-128	
EOC 60K-2	30 60	10 20	20	3	6	A	963-129	
EOC 60K-2L	30 60	10 20	20	3	9	B	963-129	
EOC 100K-2	60 150	20 50	50	3	6	A	963-129	
EOC 100K-2L	60 150	20 50	50	3	9	B	963-129	
EOC 100K-2XL	60 150	20 50	50	3	19	C	963-129	
EOC 100K-2XXL	60 150	20 50	100	0,7 - 2,7	26	D	963-129	
EOC 300K-2	150 300	50 100	100	3	9	B	963-129	
EOC 300K-2L	150 300	50 100	100	3	19	C	963-129	
Dual-range balance switches automatically to the next largest weighing capacity [Max] and readability [d]								
EOC 10K-4	6 15	0,2 0,5	5	3	7	A	963-128	
EOC 30K-4S	15 35	0,5 1	10	3	9	A	963-128	
EOC 30K-4	15 35	0,5 1	10	3	9	B	963-128	
EOC 60K-3	30 60	1 2	20	3	6	A	963-129	
EOC 60K-3L	30 60	1 2	20	3	9	B	963-129	
EOC 100K-3	60 150	2 5	50	3	7	A	963-129	
EOC 100K-3L	60 150	2 5	50	3	9	B	963-129	
EOC 300K-3	150 300	5 10	100	3	9	B	963-129	

Pictograms

 <p>Internal adjusting: Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)</p>	 <p>KERN Communication Protocol (KCP): It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems</p>	 <p>Suspended weighing: Load support with hook on the underside of the balance</p>
 <p>Adjusting program CAL: For quick setting up of the balance's accuracy. External adjusting weight required</p>	 <p>GLP/ISO log: The balance displays serial number, user ID, weight, date and time, regardless of a printer connection</p>	 <p>Battery operation: Ready for battery operation. The battery type is specified for each device</p>
 <p>Easy Touch: Suitable for the connection, data transmission and control through PC, tablet or smartphone.</p>	 <p>GLP/ISO log: With weight, date and time. Only with KERN printers</p>	 <p>Rechargeable battery pack: Rechargeable set</p>
 <p>Memory: Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.</p>	 <p>Piece counting: Reference quantities selectable. Display can be switched from piece to weight</p>	 <p>Universal mains adapter: with universal input and optional input socket adapters for A) EU, CH, GB; B) EU, CH, GB, USA; C) EU, CH, GB, USA, AUS</p>
 <p>Alibi memory: Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard</p>	 <p>Recipe level A: The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out</p>	 <p>Mains adapter: 230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available</p>
 <p>Data interface RS-232: To connect the balance to a printer, PC or network</p>	 <p>Recipe level B: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display</p>	 <p>Power supply: Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request</p>
 <p>RS-485 data interface: To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible</p>	 <p>Totalising level A: The weights of similar items can be added together and the total can be printed out</p>	 <p>Weighing principle: Strain gauges: Electrical resistor on an elastic deforming body</p>
 <p>USB data interface: To connect the balance to a printer, PC or other peripherals</p>	 <p>Percentage determination: Determining the deviation in % from the target value (100 %)</p>	 <p>Weighing principle: Tuning fork: A resonating body is electromagnetically excited, causing it to oscillate</p>
 <p>Bluetooth* data interface: To transfer data from the balance to a printer, PC or other peripherals</p>	 <p>Weighing units: Can be switched to e.g. nonmetric units at the touch of a key. See balance model. Please refer to KERN's website for more details</p>	 <p>Weighing principle: Electromagnetic force compensation: Coil inside a permanent magnet. For the most accurate weighings</p>
 <p>WiFi data interface: To transfer data from the balance to a printer, PC or other peripherals</p>	 <p>Weighing with tolerance range: (Checkweighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model</p>	 <p>Weighing principle: Single cell technology: Advanced version of the force compensation principle with the highest level of precision</p>
 <p>Control outputs (optocoupler, digital I/O): To connect relays, signal lamps, valves, etc.</p>	 <p>Hold function: (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value</p>	 <p>Verification possible: The time required for verification is specified in the pictogram</p>
 <p>Analogue interface: to connect a suitable peripheral device for analogue processing of the measurements</p>	 <p>Protection against dust and water splashes IPxx: The type of protection is shown in the pictogram</p>	 <p>DAKkS calibration possible (DKD): The time required for DAKkS calibration is shown in days in the pictogram</p>
 <p>Interface for second balance: For direct connection of a second balance</p>	 <p>Factory calibration (ISO): The time required for Factory calibration is shown in days in the pictogram</p>	 <p>Package shipment: The time required for internal shipping preparations is shown in days in the pictogram</p>
 <p>Network interface: For connecting the scale to an Ethernet network</p>	 <p>Pallet shipment: The time required for internal shipping preparations is shown in days in the pictogram</p>	 <p>Pallet shipment: The time required for internal shipping preparations is shown in days in the pictogram</p>

*The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.

KERN – Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg - 2500 kg. In combination with a DAKkS calibration certificate the best pre-requisite for proper balance calibration.

The KERN DAKkS calibration laboratory today is one of the most modern and best-equipped DAKkS calibration laboratories for balances, test weights and force-measurement in Europe.

Thanks to the high level of automation, we can carry out DAKkS calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DAKkS calibration of balances with a maximum load of up to 50 t
- DAKkS calibration of weights in the range of 1 mg - 2500 kg
- Volume determination and measuring of magnetic susceptibility (magnetic characteristics) for test weights
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DAKkS calibration certificates in the following languages DE, EN, FR, IT, ES, NL, PL
- Conformity evaluation and reverification of balances and test weights

Your KERN specialist dealer: