



Compact material thickness gauge with external sensor

Features

- **External sensor** for difficult-to-access measuring points
- **Data interface RS-232** included
- **Base plate for adjustment** incorporated
- **Delivered in a robust carrying case**
- **Selectable measuring units:** mm, inch

Technical data

- Precision: 0,5 % of [Max] + 0,1 mm
- Dimensions W×D×H 120×65×30 mm
- Battery operation, batteries standard 4× 1.5V AAA, AUTO-OFF function to preserve batteries
- Net weight approx. 0,164 kg
































Accessories

- **Software**, interface cable included, SAUTER ATD-01
- **External sensor**, 5 MHz, \varnothing 6 mm, for thin test materials: Measuring range (steel) 1–50 mm, SAUTER ATB-US01
- **External sensor**, 5 MHz, \varnothing 12 mm, for hot test materials: Measuring range (steel) 1–225 mm at normal temperatures, 4–100 mm at temperatures of up to 300 °C, SAUTER ATB-US02
- **External sensor**, 5 MHz, \varnothing 8 mm, SAUTER ATB-US06
- **External sensor**, 5 MHz, \varnothing 10 mm, SAUTER ATU-US09
- **External sensor**, 5 MHz, \varnothing 10 mm, transducer at an angle of 90°, SAUTER ATU-US10
- **Ultrasound contact gel**, standard, can be reordered, approx. 60 ml, SAUTER ATB-US03

| | | | | | |
|----------|--|--|--|--------|--|
| STANDARD | | | | OPTION | |
| | | | | | |

| Model | Measuring range | Readout | Sensor | Sound velocity | Option | |
|----------------------|-----------------|-----------|----------------------------|----------------|----------------------------------|--|
| | | | | | Factory calibration certificates | |
| SAUTER | [Max] mm | [d] mm | | m/sec | KERN | |
| TD 225-0.1US. | 1,2–225 | 0,1 | 5 MHz \varnothing 8 mm | 500–9000 | 961-113 | |

Datasheet_TD-US_V1

| | | | | | |
|--|---|---|---|---|---|
|  | Adjusting program (CAL): For quick setting of the balance's accuracy. External adjusting weight required. |  | Control outputs (optocoupler, digital I/O): to connect relays, signal lamps, valves, etc. |  | Rechargeable battery pack: rechargeable set. |
|  | Calibration block: standard for adjusting or correcting the measuring device. |  | Analogue interface: to connect a suitable peripheral device for analogue processing of the measurements. |  | Mains adapter: 230V/50Hz in standard version for EU. On request GB, AUS or USA version available. |
|  | Peak hold function: capturing a peak value within a measuring process. |  | Statistics: using the saved values, the device calculates statistical data, such as average value, standard deviation etc. |  | Power supply: Integrated, 230V/50Hz in EU. More standards e.g. GB, AUS or USA on request. |
|  | Scan mode: continuous capture and display of measurements. |  | PC Software: to transfer the measurements from the device to a PC. |  | Motorised drive: The mechanical movement is carried out by an electric motor. |
|  | Push and Pull: the measuring device can capture tension and compression forces. |  | Printer: a printer can be connected to the device to print out the measurements. |  | Motorised drive: The mechanical movement is carried out by a synchronous motor (stepper). |
|  | Length measurement: captures the geometric dimensions of a test object or the movement during a test process. |  | GLP/ISO record keeping: of measurements with date, time and serial number. Only with SAUTER printers. |  | Fast-Move: the total length of travel can be covered by a single lever movement. |
|  | Focus function: increases the measuring accuracy of a device within a defined measuring range. |  | Measuring units: Weighing units can be switched to e.g. non-metric at the touch of a key. Please refer to website for more details. |  | DAkkS calibration possible: The time required for DAkkS calibration is shown in days in the pictogram. |
|  | Internal memory: to save measurements in the device memory. |  | Measuring with tolerance range (limit-setting function): Upper and lower limiting can be programmed individually. The process is supported by an audible or visual signal, see the relevant model |  | Factory calibration: The time required for factory calibration is specified in the pictogram. |
|  | Data interface RS-232: bidirectional, for connection of printer and PC. |  | ZERO: Resets the display to "0". |  | Package shipment: The time required for internal shipping preparations is shown in days in the pictogram. |
|  | Data interface USB: To connect the balance to a printer, PC or other peripheral devices. |  | Battery operation: Ready for battery operation. The battery type is specified for each device. |  | Pallet shipment: The time required for internal shipping preparations is shown in days in the pictogram. |
|  | Data interface Infrared: To transfer data from the balance to a printer, PC or other peripheral devices. | | | | |

Your SAUTER specialist dealer: