

# **GLC**

# HIGH-PRECISION GLC SERIES DIGITAL LOAD CELL



Very high performance digital load cell, stainless steel case and electromagnetic sensor technology. Fast and repeatable, it allows to create very high performance weighing systems. Ideal for industrial automation. IP65 protection rating.

#### Working in cooperation with:

VETEK AB

HANTVERKSVÄGEN 15 - 76493 - VÄDDÖ - SWEDEN Tel. +46176-208920, info@vetek.com, www.vetek.com The best solution for advanced industrial applications

### **TECHNICAL FEATURES**

- Stabilization time approx. 0.4 sec.
- Update frequency: 100Hz.
- RS485/RS232C interface, from 1200 to 38.4kbps.
- Stainless steel casing.
- Remote calibration.
- Power supply: +24VDC ± 10%, 0.1A.
- Working temperature: 10°...30°C
- · Relative ambient humidity: 80% or less (non-condensing)
- Warm up time: 1 hour
- Temperature drift: ± 2 ppm/°C or less
- Overload protection level GLC-620: 300% F.S.
- Overload protection level GLC-3200. 150% F.S.
- IP65 protection rating (with RSCBGLC cable).

### **CONNECTABLE WEIGHT INDICATORS**

- The GLC load cell can be connected to 3590EGT series weight indicators with the GLCKIT option and the following softwares:
- - AF01: Totalization and formula weighing
- - AF02: Piece/quantity counting
- · AF04: Statistical check of prepackaged goods
- - BATCH: Software for multicomponent dosage systems in loading and unloading

## **VERSIONS**

Available versions					
	Piatto	Max	d	Linearità	Ripetibilità
Codice	Max (mm)	(g)	(g)	(g) +/-	(g)
GLC620	Ø 80 mm	620	0,001	0,002	0,001
GLC3200	Ø 80 mm	3200	0,01	0,02	0,1





DINI ARGEO FRANCE sarl France DINI ARGEO GMBH Germany DINI ARGEO UK Ltd United Kingdom DINI ARGEO WEIGHING INSTRUMENTS Ltd China DINI ARGEO OCEANIA Australia



#### **COMPANY HEADQUARTERS**

Via Della Fisica, 20 41042 Spezzano di Fiorano Modena • Italy Tel. +39.0536 843418

#### **VETEK AB**

HANTVERKSVÄGEN 15 - 76493 - VÄDDÖ - SWEDEN

 $Tel. \ +46176\hbox{-}208920, in fo@vetek.com, www.vetek.com$ 

SALES AND TECHNICAL ASSISTANCE SERVICE